

Horizontal Laboratory Planetary Ball Mill



서울특별시 금천구 가산디지털1로84 에이스하이엔드타워8차 408호
한국코프로텍(주) Tel 02-6264-5745 / Fax 02-6264-5747
www.korpro.com / www.koreaprocess.com / www.korpromall.com

Large Type Horizontal Laboratory Planetary Ball Mill

Overview

KH series planetary ball mill has four ball grinding tanks installed on one turntable. When the turntable rotates, the tank axis makes planetary movements and the balls in the tanks grinds and mixes samples in high speed movement. The product can smash and blend various products of different materials and granularity with dry or wet methods. Minimum granularity of grinded products can be as small as 0.1 micron (i.e.) $1.0 \times 10^{-4} \text{mm}$.



Design of Sliding Door

All machines over 60L are designed with doubleacting doors



Distinct designed gear with good stability and lower noise.

Distinct gear with noise of 15-20db less than that of the same model.



Grinding mill structure

Both ends of double disks support holder structure and grinding effects are moer even

Large Type Horizontal Laboratory Planetary Ball Mill

Working Principle

KH series planetary ball mill has four ball grinding tanks installed on one turntable. When the turntable rotates, the tank axis makes planetary movements, the balls and samples inside the tanks are impacted strongly in high speed movement, and samples are eventually ground into powder. A variety of different materials can be ground by the mill with dry or wet method. Minimum granularity of ground powder can be as small as 0.1 μ m.



Feature

- Easy operation.
- Unique gear with low noise.
- Horizontal structure of the mill pot avoids materials sinking to the bottom.

Advantages of Horizontal Planetary Ball Mill

- Stable revolving speed of the gear transmission ensures the consistency and repeatability of the experiment.
- Planetary movement principle is adopted in the machine, which has high speed, large energy, high efficiency, small Granularity.
- Four powder samples from different sizes and different materials can be produced at one time.
- The machine is controlled by frequency converter; you may choose ideal rotating speed according to expected experimental result. The converter is equipped with device of under voltage and over-current to protect the motor.
- The planetary ball mill has functions of timing power off, self-timing forward and reversal rotating. You may choose freely any operation modes of one-way direction, alternation, succession, and timing according to experimental needs so as to improve efficiency of grinding.
- Technical features of Tencan Ball Mill: Low center of gravity, stable performance, compact structure, easy operation, reliable safety, lower noise, small loss.
- Safety switch is installed on the machine to prevent safety accident if the safety cover is opened while machine is running.

Large Type Horizontal Laboratory Planetary Ball Mill

Application Cases of Planetary Ball Mill



Before grinding



After grinding

Material : Active carbon
Material weight : 50g
Mill Jar & Balls : Corundum mill jars and zirconia balls
Grinding method : Dry grinding
Rotation speed : 560rpm
Applied equipment : Planetary ball mill Model No.XQM-0.4A
Total volume : 1000mlx4=4000ml
Grinding time : 2hours
Granularity : 2 μ m



Before grinding



After grinding

Material : Kaolin
Material weight : 500g
Mill Jar & Balls : PTFE
Grinding method : Dry grinding
Rotation speed : 450rpm
Total volume : 1Lx4=4L
Spent time : 1hour 20 minutes
Feed size : 2mm
Granularity of output : 100 μ m



Material : Green tea (dry)
Material weight : 0.25kg
Mill Jar & Balls : Stainless steel
Grinding method : Dry grinding
Applied equipment : Planetary ball mill Model No.XQM-2
Total volume : 0.5Lx4=2L
Spent time : 1hour

Application Technical parameter

Drive Mode	Gear drive and belt drive
Operation Mode	Two or four grinding jars working together
Maximum Loading Capacity	2/3 of the capacity of milling jar
Feeding Size	Soil material \leq 10mm, other materials \leq 3mm
Output Granularity	Smallest granule reaches 0.1 μ m
Rotational Speed Ratio	1/2
Max. Continuous Operating Time	72hours
Optional Modes of Speed Control	Frequency converter and automatic timing control
Materials of Jar	Stainless steel, agate, nylon, corundum, zirconia, etc

Large Type Horizontal Laboratory Planetary Ball Mill

Technical Parameter Table

Parameters of Horizontal Planetary Ball Mill (Heavy Type)								
Model No	Power (KW)	Voltage	Dimension (mm)	Revolution Speed (rpm)	Rotation Speed (rpm)	Total Timing (min)	Noise ≤db	Alternating Run Time of Forward & Reversal Rotation(min)
KH-2-6	1.5	220V-60Hz	1220x620x810	35-335	70-670	1-9999	60±5	1-999
KH-8	1.5	220V-60Hz	1320*670*920	35-290	70-580	1-9999	60±5	1-999
KH-10	1.5	220V-60Hz	1320*670*920	35-290	70-580	1-9999	60±5	1-999
KH-12	1.5	220V-60Hz	1320*670*920	35-290	70-580	1-9999	60±5	1-999
KH-16	3	380V-60Hz	1530*750*960	30-240	60-480	1-9999	60±5	1-999
KH-20	4	380V-60Hz	1620*840*1040	25-215	50-430	1-9999	60±5	1-999
KH-40	5.5	380V-60Hz	1770*1050*1100	25-215	50-430	1-9999	60±5	1-999
KH-60	7.5	380V-60Hz	1860*1050*1280	20-206	50-310	1-9999	60±5	1-999
KH-100	11	380V-60Hz	2100*1150*1370	35-193	50-290	1-9999	60±5	1-999









Measurement of Heavy Type HOrizontal Planetary Ball Mill				
Model No	Power(KW)	Speed Control Mode	Net Weight(kg)	Dimensions(mm)
KH-2-6	1.5	Frequency Control	256	1220x620x810
KH-8	1.5	Frequency Control	370	1320x670x920
KH-10	1.5	Frequency Control	370	1320x670x920
KH-12	1.5	Frequency Control	370	1320x670x920
KH-16	3	Frequency Control	440	1220x620x810
KH-20	4	Frequency Control	700	1620x840x1040
KH-40	5.5	Frequency Control	760	1770x860x1100
KH-60	7.5	Frequency Control	1020	1860x1050x1280
KH-100	11	Frequency Control	1160	2100x1150x1370

Available Size of Mill Jar for Horizontal Planetary Ball Mill (Heavy Type)				
Model No	Specifications	Volume of each matched pot	Quantity	Remarks
KH-2-6	2-6L	0.5-1.5L	4pcs	Can be matched 0.5-1L vacuum mill jar
KH-8	8L	1-2L	4pcs	Can be matched 0.5-1.5L vacuum mill jar
KH-10	10L	1.2-5L	4pcs	Can be matched 1-2L vacuum mill jar
KH-12	12L	1-3L	4pcs	Can be matched 1-2L vacuum mill jar
KH-16	16L	2-4L	4pcs	Can be matched 1-3L vacuum mill jar
KH-20	20L	2-5L	4pcs	Can be matched 2-4L vacuum mill jar
KH-40	40L	5-10L	4pcs	Can be matched 3-5L vacuum mill jar
KH-60	60L	10-15L	4pcs	Can be matched 5-10L vacuum mill jar
KH-100	100L	15-20L	4pcs	Can be matched 10-15L vacuum mill jar

Large Type Horizontal Laboratory Planetary Ball Mill

Accessory

We provide all kinds of mill pots in any matched size, which are made from following materials of agate, Alumina corundum ceramics, zirconia ceramics, silicon nitride ceramics, carborundum ceramics, stainless steel, high wear resistant steel, manganese steel, nylon, PU, cemented carbide, crystal glass, and etc.

Material	Volume of Mill Jar	Diameter of Mill Ball	
Stainless Steel	50ml,100ml,250ml,500ml,1L,1.5L,2L,2.5L,3L,4L	1-30mm	
Stainless Steel (for vacuum)	50ml,100ml,250ml,500ml,1L,1.5L,2L,3L,4L,5L	1-30mm	
Zirconia	50ml,100ml,250ml,500ml,1L,1.5L,2L,3L,4L	1-30mm	
Alumina	50ml,100ml,250ml,500ml,1L,1.5L,2L,3L	1-50mm	
Tungsten Carbide	50ml,100ml,250ml,500ml,1L,1.5L	3-10mm	
Agate	50ml,100ml,150ml,250ml,300ml,400ml,500ml,1L,1.5L,2L	6-35mm	
Nylon	50ml,100ml,250ml,500ml,1L,1.5L,2L,2.5L,3L,4L	\	
PU	50ml,100ml,250ml,500ml,1L,1.5L,2L,2.5L,3L,4L	\	
PTFE	50ml,100ml,250ml,500ml,1L,1.5L,2L,2.5L,3L,4L	\	